

CONTRACTOR PACKS



Polyamide (Nylon)

ECONO66

An excellent 'all round' polyamide (nylon) conduit supplied with quick and efficient Push-On connectors including locknuts.



- IP66 with fittings
- Self extinguishing
- Halogen free
- Temperature range -40°C to +120°C
- Resistant to fuels, mineral oils, lubricants, alkalis and most commercial solvents

PVC

FLEXIPACK

A good 'General Purpose' PVC conduit supplied with dual purpose connectors (fixed or swivel) including locknuts.



- IP67 with fittings
- Self extinguishing
- Temperature range -20°C to +70°C
- Shock-resistant with smooth internal surface

Polypropylene

SMART54

A low cost 'General Purpose' polypropylene conduit supplied with split fittings including locknuts.



- IP54 with fittings
- Temperature range -20°C to +105°C
- Resistant to acids, bases, inorganic salts, mineral oils and most commercial solvents

SMART66

A low cost 'General Purpose' polypropylene conduit supplied with quick and efficient Push-On connectors including locknuts.



- IP66 with fittings
- Temperature range -20°C to +105°C
- Resistant to acids, bases, inorganic salts, mineral oils and most commercial solvents



For detailed information on our full range, please consult our Website www.pma-uk.com or contact us.

